Technical data

gometer	ergoselect 600 P
Brake system	microprocessor controlled eddy current brake
Load	6-999 Watt, speed independent
Accuracy	according to DIN VDE 0750-238
Speed range	30-130 rpm
Horizontal seat adjustment	for patient heights between 150 cm and 210 cm
Patient weight (max.)	260 kg max.
Seat width	54 cm
ontrol unit	
Display / patient display	load, rpm, time, blood pressure, heart rate (LCD) / rpm (LED)
Keyboard	membrane keyboard
Graphic display (load, pulse rate)	0
xercise protocols	
User programmable	10
Fixed incremental protocols (WHO, Hollmann, etc.)	5
Manual load adjustment	•
aining protocols	
Pulse-controlled training (integrated pulse receiver)	0
Predefined performance tests	0
ptions	
Automatic blood pressure measurement	0
Oxygen saturation measurement	0
ECG amplifier (ERS Rehabilitation System)	0
terfaces	
Digital (RS-232, USB) / analog / remote start	•/0/0
ERS Rehabilitation System communication port	0
iscellaneous	
Dimensions, max. (L x W x H)	approx. 165 cm x 75 cm x 108 cm
Weight	86 kg
Power	90-265 V / 50-60 Hz / 60 VA max.

ergoselect 600



ergoline

ergoline GmbH Lindenstrasse 5 D-72475 Bitz Germany

Tel.: +49-(0)-7431 - 9894 - 0 +49-(0)-7431 - 9894 - 128 info@ergoline.com internet: www.ergoline.com

Autorizovaný obchodní a servisní partner:



DODAVATEL KOMPLETNÍ ORDINACE

internet: www.compek.cz

COMPEK MEDICAL SERVICES, s.r.o. 17. listopadu 861, 506 01 Jičín mobil: + 420 605 281 433 mobil: + 420 93 524 534 fax: + 421 2 3301 6145 e-mail: info@compek.cz complex.g internet: www.compek.sk

Development and production of all ergoline products are subject to a certified quality management system according to DIN EN ISO 13485:2003.

All products are CE-marked and fulfill the requirements of the Medical Device Directive 93/42/EEC.

Some of the illustrations in this brochure show options which must be purchased separately. The information provided is based on data valid at the date of printing. Subject to modifications.





Recumbent Ergometer

Standard O Option

comfortable

The high back rest relieves the lumbo-pelvic region during training sessions and exercise tests.

Adipose patients in particular will appreciate the extremely comfortable, wide seat.

Sturdy handgrips on either side of the seat provide added support during exercise.

upgradable

Numerous options such as automatic blood-pressure measurement, integrated ECG amplifier or connection of a POLAR® receiver allow you to upgrade the ergoselect 600 for additional applications.



flexible

The position can be quickly adjusted over a wide range simply by lifting the notch lever and even while the patient is seated.





top quality

The rugged base guarantees a long service life – its powder-coated surface is hygienic, easy to clean, resistant to chipping and scratches, and withstands disinfectants and cleaning agents.



clear layout

With two different control units you are optimally prepared for the respective exercise test conditions. The clear structure of the menus supports the intuitive use and facilitates system operation.

For exercise testing the control unit "P"offers all the necessary protocols and displays the relevant parameters.



With control panel "K" you can perform a heart-rate-controlled training with chest belt or integrated ECG amplifier.

On the large graphics display a clear waveform presents the ongoing training session.



safe

The sturdy grip bars make for safe mounting and dismounting.

adjustable

Using cranks whose length is adjustable or special pedals, you can optimally set up the ergo-meter for the desired flexion of the knee and the distance between the pedals.



ergoselect 600 Recumbent

Exceptional patients demand exceptional solutions.

Designed for a patient weight of up to 260 kg, the *ergoselect 600* allows exercise tests and cardiovascular training sessions to be performed even by obese patients.

But also elderly and handicapped patients will profit from the ergoline recumbent ergometer which is the right exercise and training unit for this patient group.

designed for patient comfort

A very comfortable step-through frame, a wide adjustment range for the seat and a large seat surface are the important prerequisites for using the ergometer on obese patients.

The high back rest relieves the lumbo-pelvic region during training sessions. Particularly patients with lumbar spine dysfunction or similar problems can exercise without suffering any pain

The system can be upgraded with interferencefree, automatic blood pressure measurement, a microprocessor-controlled function providing precise measuring values - even at high loads.

practice oriented

You can use the ergometer for convenient stand-alone operation with programmable exercise test and training protocols or you connect it to a variety of electrocardiographs, PC-based ECG systems or to the ergoline rehabilitation system *ERS*.

Training sessions precisely controlled by the patient's heart rate are one of the invaluable assets. A chest belt acquires the ECG signals which are used to control the ergometer workload to achieve a constant heart rate.

competent

The rugged mechanical construction guarantees outstanding safety and trouble-free operation, even when the ergometer is permanently in use and has to withstand high loads.

All ergoline ergometers are produced with only high quality components and, of course, satisfy all applicable standards and requirements for medical grade crank ergometers.

A network of authorized, ergoline-trained service engineers is available in your country for repairs or other service interventions (such as inspections of the measuring system).